



Amended 05 Aug. 2008

DATA SHEET *ENAMEL GLOSS PAINT*

SPECIFICATION

Use	:	Interior & Exterior
Appearance	:	High Gloss Finish
Drying Time	:	16 hours
Recoat Time	:	16 hours
Spread Rate	:	10 – 12sq m/ Litre
Cleaning	:	Mineral Turpentine
Thinning	:	Not recommended

Surface Preparation

1. Ensure surface is dry and in sound condition, free from dust, grease, oil, algae, fungus or any loose particles.

Unpainted Surfaces

1. **Cement Plaster** – prime with one coat Africote Plaster Primer followed by one coat of Africote Universal Undercoat.
2. **New Metal** – prime with one coat of Africote Universal Undercoat.
3. **Rusted Metal** – remove rust. Prime with one coat Etchkote Primer followed by one coat Africote Universal Undercoat.
4. **Wood** – prime with two coats Africote Universal Undercoat.

Previously painted surfaces

Remove all dirt and all flaking paint.

- 1 **Gloss & Enamel paints** – sand well, clean and apply one coat of Africote Universal Undercoat.
- 2 **Waterbased paints** – clean well and apply 1 coat of Africote Universal Undercoat.

3 Chalky surfaces – wash surface and apply 1 or 2 coats of Africote Paint Bonding Liquid, depending on severity of condition.

4 Poor condition surfaces – strip down and treat as new surface.

Application

1. Stir well and apply first coat unthinned.
2. Apply second coat after 16 hours.

Caution

1. Application must be even to avoid variation in gloss levels.
2. Spot touch-ups will lead to variation in gloss levels and colour.
3. Applying coats too thick can cause wrinkling and running.
4. Very cold conditions will extend drying times.

Safety

1. Keep out of reach of children.
2. Avoid swallowing. If swallowed, induce vomiting and seek medical attention immediately.
3. Avoid eye contact. In case of eye contact, rinse eyes thoroughly with water, seek medical attention immediately.
4. Allow sufficient ventilation during application.

NB: No claims will be entertained where applications are done using other manufacturers products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.