



Amended 28-09-2015

## DATA SHEET SB ROAD MARKING

### **DESCRIPTION**

Africote Solvent based Road marking is a quick drying solvent borne road line paint based on a modified alkyd resin, giving a high quality low sheen Road and Floor paint designed to give a smooth finish with the following advantages:

- Excellent water resistance
- UV Resistant
- Exterior and Interior application.
- Excellent scrub and wear resistance.

### **PREPARATION ON VARIOUS SURFACES:**

MAKE SURE SUBSTRATE/SURFACE IS FREE OF GREASE, OIL, DIRT AND DUST.

#### TREATMENT OF POWDERY AND FLAKY SURFACES

Remove all loose materials via scraping, wire brush etc. Apply a minimum of 1 coat of Africote Bonding Liquid to manufacturer's instructions.

#### SCREED & CONCRETE

SB Road marking will have excellent adhesion to these surfaces provided they where sealed 1<sup>st</sup> with one coat Africote bonding liquid, SB road marking is not Alkaline resistant and need a Alkaline resistant bonding liquid as 1<sup>st</sup> coat the screeds must also be well-cured, clean, sound and at least 21 days old.

Apply a minimum of one coat of Africote Bonding liquid to the dry surface as per manufacturer's instructions.

Follow with 2 coats SB Road Marking.

## **APPLICATION OF AFRICOTE SB Road Marking**

Thoroughly mix the contents of the tin prior to application.

Can be applied by either spray , paint roller or brush.

### **COVERAGE**

3 to 4 square metre per litre per coat for unpainted roads depending on surface. And 6 to 8 for screed and concrete

**PACKAGING:** Available in 5 and 20 Litre branded tins.

**STORAGE:** Store in dry, cool conditions and ensure bucket is sealed airtight.

**CLEANING OF TOOLS:** Wash immediately after use with Africote brush cleaner.

**SHELF LIFE:** UNOPENED = 36 Months

**COLOURS:** Brown , white , Golden yellow

### **HEALTH AND SAFETY**

Contact with product may cause irritation to sensitive skin. Wear suitable hand and eye protection.

### **FIRST AID**

EYES Do not rub. Flush with plenty of water. Seek medical advice.

SKIN Wash thoroughly with soap and water. Wash immediately after handling. If condition develops seek medical advice.

NB: **No** claims will be entertained where applications are done using other manufacturer's products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

**NB:** Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.