



Unit 22 Sunview Centre
7 North Reef road
Bedfordview
P.O Box 357
Bedfordview,2008
South Africa
011 2017300

Amended APRIL 2020

DATA SHEET-All in ONE MATT ACRYLIC PVA

Description:

Africote's All in One matt Acrylic PVA is a 3 in1 One coat, Water based paint system , it's specifically designed to be a One coat Plaster Primer , Undercoat and Top coat all in one. This system is based on a modified styrene acrylic polymer and has built in mica for strength. All in one convenient package.

Principal Characteristics:

- Superior opacity and Excellent adhesion.
- Only one coat is required.
- Good application and sealing properties.
- Both for interior and exterior applications
- Fully washable after 7 days cure.
- Suitable for use on masonry plaster and concrete and previously sound painted surfaces.
- Cannot prevent lateral or rising damp.
- Covers hairline cracks and long lasting.

Surface Preparation:

Plaster work must be smooth and uniformly plastered. Ensure surface is dry and in sound condition, free from dust, grease, oil, algae, fungus (use Africote Anti-fungal cleaner) or any loose particles.

Surface moisture content must be less than 15%, before and during the application of Africote All in One matt Acrylic PVA. Stir well and apply.

Substrate temperature should be between 10°C and 30°C

Maximum relative humidity during application and curing is 85%

Due to there is always a possibility of colour variation from batch to batch, ensure to order sufficient paint of the same batch number to complete your project.

Application:

Reminder always cut in your edges first, prior to rolling and ensure you spread evenly. Then over coating existing painted surfaces make sure they are sound and not flaking or powdering, the All in one will not bind these substrates resulting in total failure of the paint system.

It is recommended to follow std. substrate paint preparations before trying to overcoat these types of

Substrates. Do not apply during cold (10 degrees or wet weather)

Basic data:

Drying Time : 40min. (touch dry)

Full cure : 7 days

Spread Rate : 4 – 6sq m/ Litre

(Depending on the porosity of the substrate /surface)

Cleaning : Water

Thinning : Not recommended

Scrub resistance : 50 000 plus scrubs

Coverage: 5-7 m2 per 1L

Packaging: 5lt, 20lt

Shelf Life: UNOPENED = 12 Months. Store in a cool, dry place.

Safety: Keep out of reach of children.
Avoid swallowing. If swallowed, induce vomiting and seek medical attention immediately.
Avoid eye contact. In case of eye contact, rinse eyes thoroughly with water, seek medical attention immediately.
Allow sufficient ventilation during application.

Colours: Available in White and 11 STD colours

Finish: Matt finish

DISCLAIMER:

For best colour and sheen consistency, it is highly recommended to use the same batch number. As batches may differ from final colour appearance ie: sheen, texture, colour and light reflections, application, surface texture and preparation. When doing any type of touch up work, paint corner to corner Africote will not entertain any claims otherwise. NB: **No** claims will be entertained where applications are done using other manufacturer's products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.