



Amended 30 Mar. 2017

DATA SHEET - FILL A CRACK

PRODUCT DESCRIPTION, USES AND ADVANTAGES

Fine white cementitious powder for filling indentations and cracks.

Properties of the product:

Will bond to bricks, plaster and similar construction materials. Can be sanded and/or painted.

Surface Preparation & Inspection

Remove enamel paint. Sand or wire brush surface thoroughly.

Cracks can be cleaned with a spray of water to remove dust and dirt. This will also moisten the substrate.

MIXING AND APPLICATION

Place 1 part of water in a clean container. Slowly add 2 ½ parts of Fill a Crack while mixing thoroughly. Mix to a smooth paste.

Do not mix more than can be used in 30 minutes.

APPLICATION

Small cracks should be filled as deep as possible by pressing the paste into the crack with a putty knife or similar tool.

Larger cracks and holes should be filled with multiple layers. Do not apply more than 3 mm thick per layer.

Allow 3 hours or longer between layers.

Fill cracks and holes to just above surface level.

When completely dry (about 5 hours) Fill a Crack can be sanded or painted.

Cleaning of Tools Use tap water. Clean immediately after use.

Packaging	500 gram
	1 Kg
	5 Kg
	30 Kg

Shelf Life	6 months
-------------------	----------

GENERAL INFORMATION

Apply a coat of Africote Plaster Primer over Fill a Crack prior to painting. Note that Fill a Crack has a smooth finish. If a wide crack is repaired in rough plaster, the smooth finish will mirror through. This must be taken into account.

Being a cement-based product, Fill a Crack pockets should be stored well away from any moisture. Keep pockets sealed and off the floor. For this reason the shelf life is limited to 6 months.

HEALTH AND SAFETY

This product contains fine cement and aggregates. Avoid inhalation and contact with the product.

Contact may cause irritation to sensitive skin. Wear suitable protective clothing, such as gloves.

In case of insufficient ventilation, wear suitable respiratory protection,

FIRST AID

Eyes In case of contact with eyes do not rub. Immediately flush with plenty of water.

Skin Wash thoroughly with soap and water.

Inhalation Move to fresh air.

In all cases, if symptoms persist or develop, seek medical attention.

DO NOT TAKE INTERNALLY

KEEP OUT OF REACH OF CHILDREN

THIS PRODUCT IS NOT FLAMMABLE

NB: **No** claims will be entertained where applications are done using other manufacturers products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.