

Amended SEPT 2025

DATA SHEET- GZC Fine and GZC Coarse

DESCRIPTION:

GZC Coarse acrylic textured coating gives a coarse/scratch effect having deep scratch lines like old, coloured plaster. GZC Fine has a finer or smoother finish.

GZC Coarse and Fine are made from binding copolymer resin, coloured fine grain marble and hard aggregates including granite and quartz and special additives to help with application and preservation.

SURFACE PREPARATION:

- STEP 1: Prepare areas to allow continuous application until architectural impediments are encountered (string courses, corners flights). The surface must be dry and smooth before starting application. A bonding liquid must be applied if there are any loose or powdery surfaces.
- STEP 2: Apply a primer coat dilute GZC 30% with water, where there is a distinct colour difference between the substrate and the GZC colour chosen.
- STEP 3: The 2nd coat is undiluted and easily applied using a trowel, spreading the product with even thickness, and levelling off the surface exerting an even pressure.
- STEP 4: Wash trowel from time to time taking care not to wet the wall.
- STEP 5: Float using a wooden or plastic trowel to desired effect. (Circular or straight scratch)

MIXING INSTRUCTIONS:

Ready for use.

The product is left to dry for approximately 24 hours. Drying time may vary due to atmospheric temperatures and humidity. Do not apply in rainy weather.

New plaster moisture content of 4% or below

DISCLAIMER:

For best colour and sheen consistency, it is highly recommended to use the same batch number. As batches may differ from final colour appearance ie: sheen, texture, colour and light reflections, application, surface texture and preparation. When doing any type of touch up work, paint corner to corner Africote will not entertain any claims otherwise. Do not apply if there is a possibility of dew or rain within the next 4 hours. Do not apply during cold (10 degrees or wet weather)

THIS PRODUCT IS SUITABLE FOR:

Fine plasters	Concrete
Prefabricated elements	Pebbledash
Old paint	Insulating panels.

Colours:

8 Standard colours

Strutturato available in bases refer relevant datasheet.

PACK SIZE & COVERAGE:

20 Litre: 6M2 Per bucket
MASS: 32.50KG

SHELF LIFE: This product has a shelf life of 3 months unopened.

STORAGE: Keep in a dry place below 25° - away from direct sunlight.

CLEANING OF TOOLS: Wash immediately after use with water.

HEALTH AND SAFETY:

This product contains fine cement and aggregates. Avoid inhalation and contact with the product. Contact may cause irritation to sensitive skin. Wear suitable protective clothing, such as gloves etc. Ensure that application areas are well ventilated.

In case of insufficient ventilation, wear suitable respiratory protection.

Wear a dust mask when mixing the dry powder initially.

Wash thoroughly immediately after handling.

FIRST AID:

Eyes: In case of contact with eyes do not rub. Immediately flush with plenty of clean water.

Skin: Wash thoroughly with soap and water.

Inhalation: Move to fresh air.
If symptoms persist or develop, or if ingested, seek medical attention.

DO NOT TAKE INTERNALLY **KEEP OUT OF REACH OF CHILDREN**
THIS PRODUCT IS NOT FLAMMABLE

NB: **No** claims will be entertained where applications are done using other manufacturer's products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.