



Amended Oct 2017

DATA SHEET - PLASTER PRIMER – Pigmented.

DESCRIPTION:

Africote Plaster Primer is an off-white, modified alkyd, alkali resistant, solvent-based primer. Good adhesion. As an alkali resistant primer on raw plaster or cement bricks. To help bind powdery or friable surfaces before painting. Internal and external application.

SURFACE PREPARATION:

Make sure all surfaces are as dust free as possible.
All surfaces must be dry and clean before application.
Ensure plaster surfaces are fully cured and at least 28 days old.

Gypsum plaster:

Apply 1 coat Plaster Primer

Method of application onto raw plaster:

Apply one coat of Africote Plaster Primer.

GENERAL APPLICATION:

Use a paint brush or mohair roller to apply. Leave for 24 hours before applying a water-based paint such as Liquid Naturals, and 16 hours before applying a solvent-based paint. The Plaster primer should be over coated within a maximum of one week.

COVERAGE: 5 to 10 square meter per litre per coat depending on surface porosity.

COLOUR: Off-white.

PACKAGING: 5 and 20 litre branded metal containers.

SHELF LIFE: 12 Months in properly sealed container. **Stir well before use.**

CLEANING OF TOOLS: Wash immediately after use with mineral turpentine.

HEALTH AND SAFETY:

This product contains solvent. Avoid inhalation. Contact with wet product may cause irritation or burns to sensitive skin. Wear suitable protective clothing, gloves, and eye/face protection. In case of insufficient ventilation, wear suitable respiratory protection (cartridge type respiratory mask).

FIRST AID:

Eyes: In case of contact with eyes do not rub. Immediately flush with plenty of water. Seek medical attention.

Skin: Wash thoroughly with soap and water. Remove soiled clothing.

Inhalation: Move to fresh air.

If symptoms persist or develop, or if ingested, seek medical attention. Wash thoroughly immediately after handling.

DO NOT TAKE INTERNALLY

KEEP OUT OF REACH OF CHILDREN

THIS PRODUCT IS FLAMMABLE - Take suitable precautions.

NB: **No** claims will be entertained where applications are done using other manufacturers products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.