



Patio & Pave

- Natural Range -
Inspired by Namibia



GINGER BREAD



RHINO



DAWN



SANDSTONE



DUSK



ELEPHANT GREY



colours may vary slightly from those shown on this card.

For further information please call our Technical Department on (011) 201 7300



Patio & Pave

- Natural Range -
Inspired by Namibia

DESCRIPTION:

Africote Patio & Pave is a high quality, low sheen floor coating, designed to give a smooth finish with the following advantages:
Excellent water resistance
UV Resistant
Exterior and Interior application.
Excellent scrub and wear resistance.

PREPARATION ON VARIOUS SURFACES:

MAKE SURE SUBSTRATE/SURFACE IS FREE OF GREASE, OIL, DIRT AND DUST.

TREATMENT OF POWDERY AND FLAKY SURFACES

Remove all loose materials via scraping, wire brush etc.

SCREED & CONCRETE

Patio & Pave will have excellent adhesion to these surfaces provided they are well-cured atleast 28 days old, clean, sound and at least 28 days old.

If there is any doubt that the surface has not been cured, wet down the surface 3 times a day for a minimum of 3 days prior to application. This will ensure better hydration of the cement. Follow with 2 coats Patio & Pave.

SURFACES PREVIOUSLY PAINTED WITH WATER BASED PAINTS

If the paint is relatively new and still clean, the surface must be well swept, hose down the area to be painted, allow at least 1 hour drying time prior to coating.

If the surface shows any sign of dirt or contamination, it should be scrubbed clean with Africote General purpose degreaser or Africote's Acid wash, and then thoroughly rinsed with water. Surface must be clean and dry prior to painting.

APPLICATION OF AFRICOTE PATIO & PAVE

Thoroughly mix the contents of the bucket prior to application.

Apply Africote Patio & Pave with a good quality sheepskin roller or paintbrush.

Allow at least 12 hours before over coating.

Basic data:

Packaging : 1lt, 5lt, 20lt

Shelf Life : Opened - 12 months, Store in dry, cool conditions and ensure bucket is sealed airtight.

Spread Rate : First coat: 5 to 8 square metre per litre per coat depending on surface. Second coat: 6 to 9 square metre per litre per coat. : Water

Cleaning

Thinning is recommended to ensure quality and benefits are retained. The product must not be diluted or thinned down with water.

Safety:

1. Keep out of reach of children.
2. Avoid swallowing. If swallowed, induce vomiting and seek medical attention immediately.
3. Avoid eye contact. In case of eye contact, rinse eyes thoroughly with water, seek medical attention immediately.

NB: No claims will be entertained where applications are done using other manufacturer's products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to on-going research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.

AFRICOTE®
"Original Coatings for Africa"
Africote Factory

Johannesburg, South Africa
(t) (011) 201 7300 (f) (011) 450
1458 www.africote.co.za Email:
info@africote.co.za

Distributors Details