



**Africote – Division of Union Flooring
Tiles (Pty) LTD**
VAT: 4790102968 Reg no:
1965/005479/07
Unit 22 Sunview Centre
7 North Reef road
Bedfordview
P.O Box 357
Bedfordview, 2008
South Africa
011 201 7300

DATA SHEET

Ammended April 2022

ELEGANT MIDSHEEN PURE ACRYLIC PAINT

DESCRIPTION

Africote Elegant midsheen is a high-quality medium-sheen pure acrylic paint designed to give a smooth finish with the following advantages:

Exterior and Interior application. UV Resistance. Very low dirt retention. Excellent washability.

SUITABLE SURFACES FOR APPLICATION

PREPARATION ON VARIOUS SURFACES:

MAKE SURE SUBSTRATE/SURFACE IS FREE OF GREASE, OIL, DIRT AND DUST.

RAW PLASTER AND BRICKS

Elegant midsheen will have excellent adhesion to these surfaces provided they are well-cured, clean, sound, new plaster must be at least 28 days old.

TREATMENT OF POWDERY AND FLAKY SURFACES

Remove all loose materials via scraping, wire brush etc. Apply a one coat Africote Bonding Liquid.

SURFACES TREATED WITH GYPSUM (Rhino lite)

Apply 1 coat of Africote Plaster Primer to manufacturer's instructions.

RAW PLASTER AND BRICKS

Apply 1 coat of Africote plaster Primer to manufacturer's instructions.

For **Coastal** and high moisture areas use Africote Plaster Primer as the first coat on raw plaster.

PLASTER WITH CHASE AND PATCH MARKS.

If the surface is not properly prepared the chase and patch marks will mirror through, when painted. Apply Africote Fillercrack and spot prime x 2 coats with Africote primer. Recoat corner to corner Elegant Midsheen.

SURFACES PREVIOUSLY PAINTED WITH WATER BASED PAINTS

If the paint is relatively new and still clean, the surface must be well dusted by wiping with a clean damp cloth.

If the surface shows any sign of dirt or contamination, it should be scrubbed clean with Africote Anti-fungal wash. Surface must be clean and dry prior to painting.

Old powdery PVA surfaces that are still sound must be thoroughly sanded and then wiped clean with a damp cloth as a minimum treatment. Alternatively sand lightly, remove dust, spot prime with 1 coat of Africote Bonding liquid.

APPLICATION OF AFRICOTE ELEGANT MIDSHEEN

Thoroughly mix the contents of the bucket prior to application. Apply Africote Elegant Midsheen with a good quality roller or paintbrush.

Allow at least 6 hours at 23 degrees before over coating. Drying times will be extended during cold, wet or humid conditions. Do not apply during cold (10 degrees or wet weather)

DISCLAIMER

For best colour and sheen consistency, it is highly recommended to use the same batch number. As batches may differ from final colour appearance ie: sheen, texture, colour and light reflections, application, surface texture and preparation. When doing any type of touch up work, paint corner to corner. Africote do not guarantee colour fastness, overtime all colour's fade or at least lose their intensity it just depends on how harsh or exposed to environmental conditions that take place during the coating's lifetime. Africote will not entertain any claims otherwise.

COVERAGE

8 to 10 square metre per litre per coat depending on surface.

PACKAGING: Available in 1, 5 and 20 Litre branded plastic buckets.

STORAGE: Store in dry, cool conditions and ensure bucket is sealed airtight.

CLEANING OF TOOLS: Wash immediately after use with clean water.

SCRUB RESISTANCE: 50 000 PLUS SCRUBS

GLOSS REFLECTIVE LEVEL: 7 – 8 on 60°

SHELF LIFE: 12 Months

COLOURS: In a vast range of colours. Tintable.

HEALTH AND SAFETY: Contact with product may cause irritation to sensitive skin. Wear suitable hand and eye protection.

FIRST AID

EYES Do not rub. Flush with plenty of water. Seek medical advice.

SKIN Wash thoroughly with soap and water. Wash immediately after handling. If condition develops seek medical advice.

NB: **No** claims will be entertained where applications are done using other manufacturer's products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.