



**Africote – Division of Union Flooring
Tiles (Pty) LTD**
VAT: 4790102968 Reg no:
1965/005479/07
Unit 22 Sunview Centre
7 North Reef road
Bedfordview
P.O Box 357
Bedfordview, 2008
South Africa
011 201 7300

Jan 2018

DATA SHEET – PINK WOOD PRIMER

Description:

Pink Wood Primer is an oil-based wood primer, which is primarily used to protect all exterior timber surfaces. This product has excellent filling and sealing properties and is normally used in conjunction with a universal undercoat, and the appropriate finish coat/s of paint.

Surface Preparation:

Ensure surface is dry and in sound condition, free from dust, grease, oil, algae, fungus or any loose particles.

Product Application:

- Stir the contents thoroughly before use
- This product should be applied without thinning. If thinning is required use Mineral Turpentine
- Apply this product with a Brush or Mohair Roller
- Allow overnight drying time before applying the final coat/s of paint
- Clean tools with Mineral Turpentine
- Wooden surfaces such as garden sheds; dog kennels & pergolas that are to be painted
- Good adhesion properties
- Excellent hiding power

Caution:

Applying coats too thick can cause wrinkling and running.

Very cold conditions will extend drying times. Do not apply coatings when outside temperatures are 4 degrees and below.

Use	:	Interior & Exterior
Appearance	:	Matt Finish
Drying Time	:	16 hours
Recoat Time	:	16 hours
Spread Rate	:	8 – 10sq m/ Litre
Cleaning	:	Mineral Turpentine
Thinning	:	Not recommended

Safety:

Keep out of reach of children.

Avoid swallowing. If swallowed, induce vomiting, and seek medical attention immediately.

Avoid eye contact. In case of eye contact, rinse eyes thoroughly with water, seek medical attention immediately.

NB: **No** claims will be entertained where applications are done using other manufacturers products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.