



**Africote – Division of Union Flooring
Tiles (Pty) LTD**
VAT: 4790102968 Reg no:
1965/005479/07
Unit 22 Sunview Centre
7 North Reef road
Bedfordview
P.O Box 357
Bedfordview,2008
South Africa
011 201 7300

Amended Feb 2021

DATA SHEET - PIGMENTED SLURRY PACK

DESCRIPTION:

Africote Slurry Pack is a two-part system consisting of 30 kg of Slurry Powder – Pigmented or Natural Cement Colour. 5 litres of Slurry Bond Liquid.

SUITABLE SURFACES:

Slurry Coat assists in filling and bridging hairline cracks and prevents them “mirroring” through to the final finished coat. This product is designed for the following applications:

To provide adhesion onto pre-painted surfaces that are to receive any cement-based product. Cement Naturals, Roman Plaster and Stucco. Cement **WILL** not adhere to a painted surface.

SURFACE PREPERATION:

Make sure surface is sound and free from any powder or flaking.

If powdery treat with Africote Bonding Liquid applied to manufacturer’s instructions.

If flaky, scrape or wire brush and thoroughly spot prime with Africote bonding liquid.

MIXING INSTRUCTIONS:

You will need 2 x 20 litre buckets to adequately mix the product.

Add 5 litres of Slurry Liquid plus 11 litres of potable water to a suitable mixing vessel.

Slowly add contents of the 30 kg bag of Slurry Powder while agitating vigorously with a suitable mechanical stirrer. The mixture will need to be separated to fit into the two buckets, alternatively split the formula in two. 15kg powder, 2.5L slurry bond 5.5L water to accommodate the volume. Allow to stand (gel) for 10 to 15 minutes.

APPLICATION:

Thoroughly saturate plastered surfaces with clean water and allow to air dry.

Using a soft broom or block brush, apply Slurry Coat with a criss-cross action, working the product into all cracks and crevices. Always maintain a wet edge and complete entire wall panels in one operation.

Allow Slurry Coat to dry for 24 hours. The applied Slurry coat must not stand longer than 5 days before over-coating. Not adhering to this period may result in delamination.

Stir the Slurry Pack vigorously every 10 minutes during application. Do not make more Slurry than can be used in an hour and a half.

Coverage: 80 to 90 m²/pack

Packaging: 30Kg Polypropylene bag of Slurry Powder plus 5-litre tin of Slurry Bond Liquid

Shelf Life: 6 Months

Washing Of Tools: Clean water

Health and Safety: This product contains fine cement and aggregates. Avoid inhalation. Contact with product may cause irritation to sensitive skin. Wear suitable protective clothing, gloves, and eye/face protection. In case of insufficient ventilation, wear suitable respiratory protection.

NB: No claims will be entertained where applications are done using other manufacturers products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.