



Amended Feb 2022

DATA SHEET – WATERBASED PLASTER PRIMER INTERIOR ONLY

DESCRIPTION:

Africote water based plaster primer is a high quality medium-sheen pure acrylic primer. Interior application for excellent alkaline resistance. Good stretch properties

SUITABLE SURFACES FOR APPLICATION:

On face-brick and raw plastered walls, cement brick, block, or similar masonry finishes.

PREPARATION ON VARIOUS SURFACES:

MAKE SURE SUBSTRATE/SURFACE IS FREE OF GREASE AND OIL

FACE BRICK: Dilute first coat of WB Plaster primer by 10% with clean water.

TREATMENT OF POWDERY AND FLAKY SURFACES: Remove all loose materials via scraping, wire brush etc. spot prime with one coat Africote Bonding Liquid.

SURFACES TREATED WITH GYPSUM (Rhino lite) not recommended

PLASTER WITH CHASE AND PATCH MARKS: If the surface is not properly prepared the chase and patch marks will mirror through, when painted. Spot prime the chase marks with waterbased plaster primer then prime the entire surface, followed by 2 coats of your top coat.

OLD POWDERY SURFACES: that are still sound must be thoroughly sanded and then wiped clean with a damp cloth as a minimum treatment. Alternatively sand lightly, remove dust, spot prime with Africote Bonding liquid.

GENERAL PREPARATION:

Ensure the plaster/substrate is a minimum of 28 days old.

Make sure substrate is free of grease, oil, dust and flaking paint.

APPLICATION OF AFRICOTE WB PLASTER PRIMER:

Thoroughly mix the contents of the drum prior to application.

Apply Africote WB plaster primer with a good quality sheepskin roller or paintbrush.

Allow at least 6 hours before over coating.

Do not apply during cold (10 degrees or wet weather)

DISCLAIMER:

For best colour and sheen consistency, it is highly recommended to use the same batch number. As batches may differ from final colour appearance ie: sheen, texture, colour and light reflections, application, surface texture and preparation. When doing any type of touch up work, paint corner to corner Africote will not entertain any claims otherwise.

COVERAGE:

FIRST COAT: 6 to 8 square metre per litre per coat depending on surface.

PACKAGING: 5 and 20 Litre branded plastic drums.

STORAGE: Store in dry, cool conditions and ensure drum is sealed.

CLEANING OF TOOLS: Wash immediately after use with clean water.

SHELF LIFE: 12 Months

COLOURS: White

HEALTH AND SAFETY: Contact with product may cause irritation to sensitive skin. Wear suitable hand and eye protection.

FIRST AID:

EYES: Do not rub. Flush with plenty of water. Seek medical advice.

SKIN: Wash thoroughly with soap and water. Wash immediately after handling. If condition develops seek medical advice.

NB: **No** claims will be entertained where applications are done using other manufacturer's products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.