



Amended FEB 2021

DATA SHEET – PLATINUM XP VELVET ACRYLIC PAINT

DESCRIPTION:

Africote XP is a high-quality low sheen acrylic paint designed to give a smooth finish with the following advantages: Interior and Exterior application. Good UV resistance. Good stretch properties. Very low dirt retention. Good scrub resistance and washability.

SUITABLE SURFACES FOR APPLICATION:

PREPARATION ON VARIOUS SURFACES:

MAKE SURE SUBSTRATE/SURFACE IS FREE OF GREASE, OIL, DIRT AND DUST.

RAW PLASTER AND BRICKS:

XP Velvet will have excellent adhesion to these surfaces provided they are well-cured, clean, sound new plaster must be at least 28 days old.

TREATMENT OF POWDERY AND FLAKY SURFACES:

Remove all loose materials via scraping, wire brush etc. Apply one coat Africote Bonding Liquid.

SURFACES TREATED WITH GYPSUM (Rhino light):

Apply 1 coat of Africote Plaster Primer to manufacturer's instructions.

RAW PLASTER AND BRICKS:

Apply 1 coat of Africote Plaster Primer to manufacturer's instructions.

For **Coastal** and high moisture areas use Africote Plaster Primer as the first coat on raw plaster.

PLASTER WITH CHASE AND PATCH MARKS:

If the surface is not properly prepared the chase and patch marks will mirror through, when painted. Apply Africote Fillercrack and spot prime with Africote Plaster Primer.

SURFACES PREVIOUSLY PAINTED WITH WATER BASED PAINTS:

If the paint is relatively new and still clean, the surface must be well dusted by wiping with a clean damp cloth. If the surface shows any sign of dirt or contamination, it should be scrubbed clean with Africote Anti-Fungal wash. Surface must be clean and dry prior to painting.

Old powdery PVA surfaces that are still sound must be thoroughly wiped clean with a damp cloth as a minimum treatment. Spot prime with 1 coat of Africote Bonding liquid on affected areas only.

APPLICATION OF AFRICOTE XP VELVET:

Thoroughly mix the contents of the bucket prior to application. Apply Africote XP Velvet with a good quality sheepskin roller or paintbrush. Allow at least 6 hours at 23 degrees before over coating. Drying times will be extended during cold, wet, or humid conditions. Do not apply during cold (below 10 degrees or wet weather).

COVERAGE:

FIRST COAT: 6 to 8 square metre per litre per coat depending on surface.

SECOND COAT: About 10 square metre per litre per coat.

PACKAGING: 1, 5 and 20 Litre branded plastic drums.

SCRUB RESISTANCE: 50 000 PLUS SCRUBS

GLOSS REFLECTIVE LEVEL: on

STORAGE: Store in dry, cool conditions and ensure drum is sealed.

CLEANING OF TOOLS: Wash immediately after use with clean water.

SHELF LIFE: UNOPENED = 36 Months.

COLOURS and FINISH: In a vast range of colours. See your local Africote outlet. Can be painted over Liquid or Textured Naturals to give a washable textured finish.

HEALTH AND SAFETY:

Contact with product may cause irritation to sensitive skin. Wear suitable hand and eye protection.

FIRST AID:

EYES: Do not rub. Flush with plenty of water. Seek medical advice.

SKIN: Wash thoroughly with soap and water. Wash immediately after handling. If condition develops seek medical advice.

NB: No claims will be entertained where applications are done using other manufacturer's products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.

Unit 22 Sun View Centre, 7 North Reef road, Bedfordview East Germiston, P.O Box 357 Bedfordview, 2008,
South Africa

Directors: **Colin John Reeves; Roberto Paulio Ghisleni**

VIST OUR WEBSITE AT: www.africote.co.za