



Amended April 2020

DATA SHEET – AYOBA COAT MATT

DESCRIPTION:

Africote Ayoba coat is a high-quality matt styrene acrylic paint designed to give a smooth finish with the following advantages:

Interior and Exterior application for excellent alkaline resistance. Good stretch properties

SUITABLE SURFACES FOR APPLICATION:

On face-brick and raw plastered walls, cement brick, block or similar masonry finishes.

PREPARATION ON VARIOUS SURFACES:

Make sure the surface is free from dust and oils.

FACE BRICK:

Dilute first coat of Ayoba by 10% with clean water. Followed by 2 coats of Ayoba.

TREATMENT OF POWDERY AND FLAKY SURFACES:

Remove all loose materials via scraping, wire brush etc. Apply a one coat Africote Bonding Liquid.

SURFACES TREATED WITH GYPSUM (Rhino lite):

Apply 1 coat of Africote Plaster Primer to manufacturer's instructions.

PLASTER WITH CHASE AND PATCH MARKS:

If the surface is not properly prepared the chase and patch marks will mirror through, when painted. Apply Africote plaster primer to all patching prior to coating 2 coats of Ayoba matt paint.

SURFACES PREVIOUSLY PAINTED WITH WATER BASED PAINTS:

If the paint is relatively new and still clean, the surface must be well dusted by wiping with a clean damp cloth.

If the surface shows any sign of dirt or contamination, it should be scrubbed clean with sugar soap or similar cleaning method. Surface must be clean and dry prior to painting.

Old powdery PVA surfaces that are still sound must be thoroughly sanded and then wiped clean with a damp cloth as a minimum treatment. Alternatively sand lightly, remove dust, follow with 1 coat of Africote Bonding liquid.

GENERAL PREPARATION:

Ensure the plaster/substrate is a minimum of 28 days old. Make sure substrate is free of grease, oil, dust and flaking paint.

APPLICATION:

Thoroughly mix the contents of the drum prior to application. Apply Africote Ayoba coat with a good quality sheepskin roller or paintbrush. Allow at least 6 hours before over coating.

Do not apply if there is a possibility of dew or rain within the next 4 hours. Do not apply during cold (10 degrees or wet weather)

DISCLAIMER:

For best colour and sheen consistency, it is highly recommended to use the same batch number. As batches may differ from final colour appearance ie: sheen, texture, colour and light reflections, application, surface texture and preparation. When doing any type of touch up work, paint corner to corner Africote will not entertain any claims otherwise.

COVERAGE:

FIRST COAT: 6 to 8 square metre per litre per coat depending on surface.

SECOND COAT: About 8 square metre per litre per coat.

PACKAGING:

5 and 20 Litre branded plastic drums.

SCRUB RESISTANCE:

10 000 plus scrubs

STORAGE:

Store in dry, cool conditions and ensure drum is sealed.

CLEANING OF TOOLS:

Wash immediately after use with clean water.

SHELF LIFE:

12 Months

COLOURS and FINISH:

In 12 STD colours, on request can produce other colours but then with a minimum batch or pot size of 200lt. See your local Africote outlet. Finish is a washable matt finish.

HEALTH AND SAFETY:

Contact with product may cause irritation to sensitive skin. Wear suitable hand and eye protection.

FIRST AID:

EYES: Do not rub. Flush with plenty of water. Seek medical advice.

SKIN: Wash thoroughly with soap and water. Wash immediately after handling. If condition develops seek medical advice.

NB: **No** claims will be entertained where applications are done using other manufacturers products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.