



Amended OCT 2017

DATA SHEET - BONDING LIQUID – Solvent based

Description:

Africote Bonding Liquid is a clear, alkali resistant, solvent-based bonding liquid.

Uses:

To bind powdery or friable surfaces before painting. To even surface suction of paint to avoid colour variation and patches. Recommended as a first coat onto raw plaster.

Surface preparation:

Make sure all surfaces are as dust free as possible. All surfaces must be dry and clean before application. Ensure plaster surfaces are fully cured and at least 28 days old.

Method of application onto gypsum plaster: Apply 2 coats of Bonding Liquid with a minimum of 4 hours between coats. The first coat should be diluted with a maximum of 10% mineral turpentine.

Method of application onto raw plaster: Apply two coats of Africote Bonding Liquid.

Method of application onto surfaces where lime wash has been removed: Dilute with mineral turpentine. One part Bonding Liquid and 2 parts mineral turpentine. Apply 3 coats.

General application:

Use a paint brush or roller to apply. In all instances allow a minimum of 4 hours between coats of Bonding Liquid. Leave for 24 hours before applying a water-based paint such as Liquid Naturals, and 16 hours before applying a solvent-based paint.

Coverage: 6 to 8 square meter per litre per coat depending on surface.

Packaging: 5 and 20 litre branded metal containers.

Shelf life: 36 Months in properly sealed container.

Cleaning of tools: Wash immediately after use with mineral turpentine.

HEALTH AND SAFETY:

This product contains solvent. Avoid inhalation. Contact with wet product may cause irritation or burns to sensitive skin. Wear suitable protective clothing, gloves, and eye/face protection. In case of insufficient ventilation, wear suitable respiratory protection (cartridge type respiratory mask).

FIRST AID:

Eyes: In case of contact with eyes do not rub. Immediately flush with plenty of water.

Skin: Wash thoroughly with soap and water. Remove soiled clothing.

Inhalation: Move to fresh air. If symptoms persist or develop, or if ingested, seek medical attention. Wash thoroughly immediately after handling.

DO NOT TAKE INTERNALLY, KEEP OUT OF REACH OF CHILDREN, THIS PRODUCT IS FLAMMABLE - Take suitable precautions.

NB: No claims will be entertained where applications are done using other manufacturers products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.

Unit 22 Sun View Centre, 7 North Reef road, Bedfordview East Germiston, P.O Box 357 Bedfordview, 2008,
South Africa

Directors: V.P. Ghisleni, H.B. De Abreu, R.P Ghisleni
VIST OUR WEBSITE AT: www.africote.co.za