



Amended 21 Oct. 2009

DATA SHEET - BRICKSEAL

DESCRIPTION:

A styrene acrylic solution polymer with clear or slight amber appearance.

SUITABLE SURFACES:

As a Brickseal or as a bonding liquid on cementitious substrates having good penetration. Brickseal has good resistance to yellowing, dirt retention, chalking and blistering.

SURFACE PREPARATION AND INSPECTION:

Make sure all surfaces are as dust free as possible. All surfaces must be dry and clean before application. Use a paint brush or roller to apply. Product can be spray applied. If a water based paint is to be applied over the Brickseal, leave for 24 hours before applying the paint.

COVERAGE:	5 to 10 square meter per litre per coat depending on surface porosity.
COLOUR:	Clear to slight amber.
PACKAGING:	5 and 20 litre branded metal containers.
SHELF LIFE:	12 Months in properly sealed container. Stir well before use.
CLEANING OF TOOLS	Wash immediately after use with mineral turpentine.

HEALTH AND SAFETY:

This product contains solvent. Avoid inhalation. Contact with wet product may cause irritation or burns to sensitive skin. Wear suitable protective clothing, gloves, and eye/face protection. In case of insufficient ventilation, wear suitable respiratory protection (cartridge type respiratory mask).

FIRST AID:

Eyes:	In case of contact with eyes do not rub. Immediately flush with plenty of water. Seek medical attention.
Skin:	Wash thoroughly with soap and water. Remove soiled clothing.
Inhalation:	Move to fresh air.

If symptoms persist or develop, or if ingested, seek medical attention. Wash thoroughly immediately after handling.

DO NOT TAKE INTERNALLY: KEEP OUT OF REACH OF CHILDREN: THIS PRODUCT IS FLAMMABLE - Take suitable precautions.

NB: **No** claims will be entertained where applications are done using other manufacturers products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.