



Amended April 2022

DATA SHEET – FILL A CRACK

DESCRIPTION:

Fine white cementitious powder for filling indentations and cracks that will bond to bricks, plaster, and similar construction materials. Can be sanded and/or painted.

Surface Preparation:

Remove existing paint in effected areas. Sand or wire brush surface thoroughly.

Cracks can be cleaned with a spray of water to remove dust and dirt. This will also moisten the substrate.

MIXING AND APPLICATION:

Place 1 part of water in a clean container. Slowly add 2 ½ parts of Fill a Crack while mixing thoroughly. Mix to a smooth paste. Do not mix more than can be used in 30 minutes.

APPLICATION:

Small cracks should be filled as deep as possible by pressing the paste into the crack with a putty knife or similar tool. Larger cracks and holes should be filled with multiple layers. Do not apply more than 3 mm thick per layer. Allow 3 hours or longer between layers. Fill cracks and holes to just above surface level. When completely dry (about 5 hours) Fill a Crack can be sanded and painted for best results prime with Plaster Primer to avoid visible chase marks. Note that Fill a Crack has a smooth finish. If a wide crack is repaired in rough plaster, the smooth finish will mirror through. This must be considered. Being a cement-based product, Fill a Crack pockets should be stored well away from any moisture. Keep pockets sealed and off the floor. For this reason, the shelf life is limited to 6 months.

Cleaning of Tools: Use tap water. Clean immediately after use.

Packaging: 500 gram -1 Kg - 5 Kg - 30 Kg

Shelf Life 6 months

HEALTH AND SAFETY:

This product contains fine cement and aggregates. Avoid inhalation and contact with the product.

Contact may cause irritation to sensitive skin. Wear suitable protective clothing, such as gloves.

In case of insufficient ventilation, wear suitable respiratory protection,

FIRST AID:

Eyes: In case of contact with eyes do not rub. Immediately flush with plenty of water.

Skin: Wash thoroughly with soap and water.

Inhalation: Move to fresh air.

In all cases, if symptoms persist or develop, seek medical attention. DO NOT TAKE INTERNALLY

KEEP OUT OF REACH OF CHILDREN. THIS PRODUCT IS NOT FLAMMABLE

NB: **No** claims will be entertained where applications are done using other manufacturers products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.

Unit 22 Sun View Centre, 7 North Reef road, Bedfordview East Germiston, P.O Box 357 Bedfordview, 2008,
South Africa

Directors: V.P. Ghisleni, H.B. De Abreu, R.P Ghisleni

VIST OUR WEBSITE AT: www.africote.co.za