



Amended April 2022

DATA SHEET - HIGH GLOSS ENAMEL PAINT

Description:

Africote gloss enamel is a high-quality interior /exterior enamel for surfaces where a glossy durable finish is required for trims, doors windows and inside walls.

Surface Preparation:

Ensure surface is dry and in sound condition, free from dust, grease, oil, algae, fungus, or any loose particles.

Unpainted Surfaces:

Cement Plaster: prime with one coat Africote Plaster Primer followed by one coat of Africote Universal Undercoat. Finish 2 coats gloss enamel

New Metal: prime with one coat of Africote QD Red Oxide Primer. Finish 2 coats gloss enamel.

Rusted Metal: Apply Africote Rust Convertor as per manufacturer's instructions. Prime with one coat etch Primer followed by one coat Africote Universal Undercoat. Finish with 2 coats gloss enamel.

Wood: prime with two coats Africote Universal Undercoat. Finish 2 coats gloss enamel.

Previously painted surfaces:

Remove all dirt and all flaking paint.

Gloss & Enamel paints: sand well, clean and reapply gloss enamel.

Water based paints: clean well and apply 2 coats of Africote Gloss Enamel.

Chalky surfaces: wash surface and apply 1 coat of Africote Bonding Liquid, apply 2 coats gloss enamel.

Poor condition surfaces: strip down and treat as new surface.

Application:

1. Stir well and apply first coat un thinned.
2. Apply second coat after 16 hours.

SPECIFICATION:

Use: Interior

Appearance: Gloss Finish

Drying Time: 16 hours

Recoat Time: 16 hours

Spread Rate: 10 – 12sq m/ Litre

Cleaning: Mineral Turpentine

Thinning: Not recommended

Caution:

1. Application must be even to avoid variation in gloss levels.
2. Spot touch-ups will lead to variation in gloss levels and colour.
3. Applying coats too thick can cause wrinkling and running.
4. Very cold conditions will extend drying times.

Health and Safety:

1. Keep out of reach of children.
2. Avoid swallowing. If swallowed, induce vomiting, and seek medical attention immediately.
3. Avoid eye contact. In case of eye contact, rinse eyes thoroughly with water, seek medical attention immediately.
4. Allow sufficient ventilation during application.

NB: **No** claims will be entertained where applications are done using other manufacturers products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.