



Amended OCT 2019

DATA SHEET - PATIO & PAVE

DESCRIPTION:

Africote Patio & Pave is a high-quality low sheen Floor paint designed to give a smooth finish with the following advantages:

Excellent water resistance, UV Resistant, Exterior, and Interior application.

Excellent scrub and wear resistance.

SUITABLE SURFACES FOR APPLICATION:

PREPARATION ON VARIOUS SURFACES:

MAKE SURE SUBSTRATE/SURFACE IS FREE OF GREASE, OIL, DIRT AND DUST.

TREATMENT OF POWDERY AND FLAKY SURFACES:

Remove all loose materials via scraping, wire brush etc.

SCREED & CONCRETE:

Patio & Pave will have excellent adhesion to these surfaces provided they are well-cured, clean, sound and at least 28 days old.

SURFACES PREVIOUSLY PAINTED WITH WATER BASED PAINTS:

If the paint is relatively new and still clean, the surface must be well swept, hose down the area to be painted, allow at least 1 hour drying time prior to coating. If the surface shows any sign of dirt or contamination, it should be scrubbed clean with Africote Anti-fungal wash or similar cleaning method and then thoroughly rinsed. Surface must be clean and dry prior to painting.

APPLICATION OF AFRICOTE PATIO & PAVE

Thoroughly mix the contents of the bucket prior to application. Apply Africote Patio & Pave with a good quality sheepskin roller or paintbrush. Allow at least 12 hours before over coating. Drying times will be extended during cold, wet, or humid conditions. Do not apply during cold (below 10 degrees or wet weather)

COVERAGE:

FIRST COAT: 5 to 8 square metre per litre per coat depending on surface.

SECOND COAT: 6 to 9 square metre per litre per coat.

PACKAGING: Available in 1, 5 and 20 Litre branded plastic buckets.

STORAGE: Store in dry, cool conditions and ensure bucket is sealed airtight.

CLEANING OF TOOLS: Wash immediately after use with clean water.

SHELF LIFE: 12 Months

COLOURS: Brown Black Charcoal Green Red Terracotta

SCRUB RESISTANCE: 50 000 plus scrubs

HEALTH AND SAFETY:

Contact with product may cause irritation to sensitive skin. Wear suitable hand and eye protection.

FIRST AID:

EYES Do not rub. Flush with plenty of water. Seek medical advice.

SKIN Wash thoroughly with soap and water. Wash immediately after handling. If condition develops seek medical advice.

DISCLAIMER:

For best colour and sheen consistency, it is highly recommended to use the same batch number. As batches may differ from final colour appearance ie:

sheen, texture, colour and light reflections, application, surface texture and preparation. When doing any type of touch up work, paint corner to corner Africote will not entertain any claims otherwise.

NB: No claims will be entertained where applications are done using other manufacturer's products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

NB: Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.